

DC704

Flex PVC tex sil.

L 150 cm anti-twist

1/2" F x 1/2" F



CONSTRUCTION SPECIFICATIONS

- Exclusive SNAKE hose made up of:
 - non-toxic PVC substrate with textile coating;
 - external protection in transparent non-toxic crystal clear PVC;
 - brass fittings with AISI 304 stainless steel liner.


TECHNICAL SPECIFICATIONS

- Maximum working temperature: 50 °C
- Maximum working pressure: 6 Bar (bursting pressure 10 Bar)
- Flow: 23 l/min. to 3 bar
- Bend radius: 45 mm

Complete with anti-rotation connection system with seal assembled with EPDM:

A SIDE: 36 mm shiny smooth cone and anti-twist system with assembled seal

B SIDE: brass chrome-plated smooth cap covering the pinched sleeve, with assembled seal.



DIMENSIONAL SPECIFICATIONS

- Hose length: 150 cm
- Connections: G 1/2" F x G 1/2" F
- \varnothing internal hose: 9 mm
- \varnothing external hose: 14,8 mm

WE RECOMMEND CARRYING OUT MAINTENANCE ON NOZZLES AND CHROME PARTS USING A SOFT CLOTH DAMPENED WITH A LITTLE WATER. DO NOT USE ABRASIVES OR ANTI-LIMESCALE DETERGENTS.

PRODUCTION RANGE

Art.	Code	Finishing
DC704	4180349	PVC tex sil.