

DC701

Flex PVC white chrome
L 150 cm anti-twist
1/2" F x 1/2" F




CONSTRUCTION SPECIFICATIONS

- Pipe made up of:
 - non-toxic substrate with reinforced longitudinal thread;
 - available in chrome colors;
 - PVC coating and PVC crystal layer;
 - brass fittings and chrome-plated nuts, stainless steel sleeves.

TECHNICAL SPECIFICATIONS

- Maximum working temperature: 70 °C
- Maximum working pressure: 5 Bar (bursting pressure 15 Bar)
- Flow: 23 l/min. to 3 bar
- Bend radius: 45 mm

Complete with anti-rotation connection system with seal assembled with EPDM:
A SIDE: 36 mm shiny smooth cone and anti-twist system with assembled seal
B SIDE: brass chrome-plated smooth cap covering the pinched sleeve, with assembled seal.



DIMENSIONAL SPECIFICATIONS

- Hose length: 150 cm
- Connections: G 1/2" F x G 1/2" F
- Ø internal hose: 9 mm
- Ø external hose: 14,8 mm

WE RECOMMEND CARRYING OUT MAINTENANCE ON NOZZLES AND CHROME PARTS USING A SOFT CLOTH DAMPENED WITH A LITTLE WATER. DO NOT USE ABRASIVES OR ANTI-LIMESCALE DETERGENTS.

PRODUCTION RANGE

Art.	Code	Finishing
DC701	4180346	PVC white chrome